


- MICRO SNAP-IN 92715** ◇  
6 24113 9210◇  
◇ = B / W
- MICRO SNAP-IN 92730** ◇  
24113 9220◇  
◇ = B / W
- MICRO SNAP-IN 93015** ◇  
6 24113 9310◇  
◇ = B / W
- MICRO SNAP-IN 93030** ◇  
6 24113 9320◇  
◇ = B / W
- MICRO SNAP-IN 93515** ◇  
6 24113 9510◇  
◇ = B / W
- MICRO SNAP-IN 93530** ◇  
6 24113 9520◇  
◇ = B / W



**Application**

Finishing section to be used with DELTA LIGHT® rough-in housing or plasterframe

**Ceiling Thickness**

For 5/8" ceiling standard up to 7/8"

**Light source**

One 4,1W POWERLED WHITE

**Power Supply**

Current controled class 2 power supply required. (supplied with housing or plasterframe)  
Max 350mA, typical forward voltage 11,8V. Do not interconnect in parallel!

**Connector**


Housing connection through pre-installed snap-in connector

**Specification features**

- Construction powder coated aluminum
- Pre-installed springs for easy installation
- Suitable for dry and damp locations
- Protected against solid objects greater than 12mm ➡ IP20

**Dimensions**

- Height: 67mm = 2" - 5/8
- Crosssection: 300mm x 65mm = 3"-15/16 x 2"-9/16
- Ceiling Cut out: Ø48mm = Ø1"-7/8



Accessories

